



Product Information Sheet

Re-Issue Date: 01/07/13

Page 1 of 2

ALL STONE SEALER

HIGH GLOSS SURFACE SEAL

DESCRIPTION

ALL-STONE SEALER is an acrylic emulsion water borne sealer used for the sealing of slate, terracotta, sandstone, limestone, clay and cement pavers. ALL-STONE SEALER inhibits water and oil based stains while maintaining the natural appearance of the surface being sealed.

BENEFITS OF USING ALL-STONE SEALER

- Excellent adhesion to "chalky" surfaces, lightly soiled concrete, masonry and slate tiles.
- Good resistance to abrasion, water, detergents and oil based stains.
- Rapid hardness development.
- Fast set and tack-free times.
- Provides a water based alternative to solvent borne acrylics.
- Excellent gloss and levelling characteristics enabling surfaces to be sealed ranging from extremely porous tiles to dense tiles.

DIRECTIONS FOR USE

1. In order to determine the compatibility of ALL-STONE SEALER with your floor a test area of one or two tiles should be attempted before sealing the entire floor. If this finish meets your requirements continue to seal the remaining tiles.
2. Ensure that the surface to be sealed is completely clean and dry. Any stains, soil, cement or grouting present on the surface should be removed prior to sealing using LIFT OFF and TILE KLEEN as per instructions.
3. Newly laid areas require 4-6 weeks to allow mortar and grout to cure prior to sealing.
4. Allow the tiles to dry thoroughly prior to sealing by leaving for at least 24 hours after cleaning and washing.
5. Do not seal hot surfaces - all surfaces must be cool.
6. Apply three or four even generous coats of ALL-STONE SEALER using a paint brush or lambswool applicator. Allow approximately 4 hours between applications.

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied.

Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.

Australia: Tasman Chemicals Pty Ltd

Victoria: 1-7 Bell Grove Braeside Victoria 3195 Ph: 61-2-9587 6777 Fax: 61-2-9587 5255

New South Wales: Unit 12, 155 Glendenning Road Glendenning 2761 Ph: 61-2-9980 5999 Fax: 61-2-9484 8647

South Australia: 4/159 Williams Street, Beverley 5009 Ph: 61-8-8243 0644 Fax: 61-8-8243 0622

Tasmania: 1 Durham Road, Cooeee 7320 Ph: 61-3-6432 1988 Fax: 61-3-6432 1989

Western Australia: Unit 1, 23 Dillington Pass, Lansdale Pass WA 6065 Ph: 61-8-9309 2100 Fax: 61-8-9309 2511

Queensland: Unit 12/172 Redland Bay Road, Capalaba, 4157 Ph: 61-7-3245 2862 Fax: 61-7-3245 2413



Product Information Sheet

Re-Issue Date: 01/07/13

Page 2 of 2

ALL STONE SEALER

HIGH GLOSS SURFACE SEAL

DIRECTIONS FOR USE (continued)

7. Allow 24 hours for product to cure before allowing full use of the treated surface.
8. In order to gain maximum benefit from the use of ALL-STONE SEALER it is recommended that all spills and soiling materials be removed from treated floors as soon as possible after the spill using Tile Kleen.
9. Re-application of ALL-STONE SEALER may be necessary every 12 months or as necessary dependent on the traffic and soiling.
10. Brushes and application equipment may be cleaned with a hot solution of TILE KLEEN. Reseal container after use to prevent deterioration of the product.
11. As this product is used under conditions beyond our control, the seller will not be responsible for results obtained. Liability is restricted to the replacement of any material if proven faulty and the manufacturer is not responsible for any loss or damage arising from incorrect usage. Determining the suitability of the product for any intended usage shall be the sole responsibility of the user.

Coverage: 1 Litre will cover approx. 8-20 square metres per coat depending on the porosity of the tiles.

WARNING:

Do not use ALL-STONE SEALER on surfaces in areas that are exposed to ground water or salt water from swimming pools. These areas can accumulate salt deposits, causing efflorescence and flaking of the sealer

PACKAGING

- 1 Lt Polyethylene bottle
- 5 Lt Polyethylene drum
- 15 Lt Polyethylene drum

HEALTH AND SAFETY INFORMATION

See separate Health and Safety Data Sheet available on request

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied.

Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.

Australia: Tasman Chemicals Pty Ltd

Victoria: 1-7 Bell Grove Braeside Victoria 3195 Ph: 61-2-9587 6777 Fax: 61-2-9587 5255

New South Wales: Unit 12, 155 Glendenning Road Glendenning 2761 Ph: 61-2-9980 5999 Fax: 61-2-9484 8647

South Australia: 4/159 Williams Street, Beverley 5009 Ph: 61-8-8243 0644 Fax: 61-8-8243 0622

Tasmania: 1 Durham Road, Cooeee 7320 Ph: 61-3-6432 1988 Fax: 61-3-6432 1989

Western Australia: Unit 1, 23 Dillington Pass, Lansdale Pass WA 6065 Ph: 61-8-9309 2100 Fax: 61-8-9309 2511

Queensland: Unit 12/172 Redland Bay Road, Capalaba, 4157 Ph: 61-7-3245 2862 Fax: 61-7-3245 2413