



## PRODUCT INFORMATION SHEET

# SPRAY SEAL

## Tile , Stone & Grout Sealer



### Description

**SPRAY SEAL** is an aerosol that penetrates into tiles and grout making them water repellent without providing a slippery surface.

### Applications

**SPRAY SEAL** can be used to seal the following surfaces:

- Shower mortar & grout
- Quarry tiles
- Sandstone
- Terracotta
- Stone
- Limestone
- Porcelain

### Features and Benefits

- ❖ Quickly penetrate surface
- ❖ Inhibits stain absorption
- ❖ Leaves Natural Appearance
- ❖ Easy spray application
- ❖ Simple and safe to use
- ❖ Non Yellowing, UV Resistant

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied. Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.



## PRODUCT INFORMATION SHEET

# SPRAY SEAL

## Tile , Stone & Grout Sealer

### Method of Use

1. Prior to sealing with **SPRAY SEAL** ensure that the surface is thoroughly cleaned and dry and free from grease, oil, paint, acid, efflorescence and traces of grout
2. Leave area to dry for a minimum of 24 hours prior to sealing.
3. Fix all missing or broken tiles prior to sealing.
4. Do a test area to see if compatible with surface to be sealed.
5. Hold spray can approximately 15 –20 cm away from desired surface and spray in a sweeping action. Allow 5 – 10 minutes to penetrate the surface then wipe off excess with damp cloth
6. A second application may be applied after another four hours
7. Allow 24 hours for product to cure after sealing.

### COVERAGE

One can will cover approximately 25m<sup>2</sup> or 600 linear metres of grout lines dependent on porosity of the surface being treated and grout line width.

### NOTE

**SPRAY SEAL** should last up to 2 years, depending on the type of cleaning products used on the sealed area. Tasman recommend Tile Kleen as an all purpose cleaner.

**SPRAY SEAL** can be used interior or exterior.

### Packaging

- ◆ 300 gm aerosol - 12 per carton.

### Health Hazard Information

See separate Health and Safety Data Sheet, available on request.

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied. Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.